

# Plné tyče POM

Průměr	Tolerance (mm)		POM-C	POM-ELS	POM-ESD-FG	POM-10PE
(mm)	min.	max.	kg/m	kg/m	kg/m	kg/m
5	+ 0,1	+ 0,6	0,032 ●●			
6			0,045 ●●			
8		+ 0,7	0,079 ●●			
10			0,121 ●●			
12	+ 0,2	+ 0,8	0,176 ●●			
15			0,271 ●●			
16		+ 0,8	0,307 ●●			
18			0,386 ●●			
20		+ 1,0	0,474 ●●			0,460 ●
22			0,575 ●●			
25		+ 1,0	0,740 ●●			
28			0,930 ●●			
30		+ 1,2	1,060 ●●	1,053 ●		1,043 ●
32			1,210 ●●			
35		+ 1,2	1,440 ●			
36			1,520 ●●			
40		+ 1,3	1,870 ●●			1,831 ●
45	+ 0,3	+ 1,3	2,370 ●●			
50			2,920 ●●●● ●	2,900 ●	2,962 ○	2,864 ●
56		+ 1,6	3,650 ●●			
60			4,200 ○●●● ●			4,123 ●
65	+ 0,4	+ 1,6	4,920 ●●			
70			5,690 ○●●● ●			
75		+ 2,0	6,570 ●●			
80	+ 0,5	+ 2,0	7,460 ●●	7,408 ●		
85		+ 2,2	8,430 ●●			
90			9,430 ●●			
100	+ 0,6	+ 2,5	11,650 ●●			11,458 ●
110	+ 0,7	+ 3,0	14,150 ●●			
120	+ 0,8	+ 3,5	16,900 ●●			
125			18,300 ○●●			
130	+ 0,9	+ 3,8	19,800 ○●●			
140			22,900 ○●●			
150	+ 1,0	+ 4,2	26,350 ○●●			
160	+ 1,1	+ 4,5	30,000 ○●●			
165	+ 1,2	+ 5,0	31,200 ○●●			
180			37,900 ○●●			
200	+ 1,3	+ 5,5	46,800 ○●●			
210	+ 1,5	+ 6,2	51,970 ○●●			
230			61,900 ○●●			
250			72,900 ○●●			

300	0	+ 7,5	108,700	● ●			
350		+ 8,5	145,600	● ●			
400		+ 9,5	189,700	● ●			
500		+ 11,5	287,400	● ●			

## Standardní délky:

1000 / 2000 / 3000 mm

## Barvy:

- černá
- natur
- modrá (~RAL 5002)
- ◎ slonová kost
- světle modrá