

Plné tyče PP

Průměr (mm)	Tolerance průměru (mm)		PP	PP-30GF
	min.	max.	kg/m	kg/m
10	+0,1	+0,6	0,078 	
12	+0,2	+0,7		
15		+0,8		
20		+1,0	0,312 	0,391 
25		+1,1	0,484 	0,606 
30		+1,2	0,694 	
35	+0,2	+1,3	0,947 	
40		+1,5	1,230 	1,541 
45	+0,3	+1,7	1,560 	
50		+2,0	1,930 	2,418 
55			2,300 	
60		+2,3	2,770 	3,470 
65			3,170 	
70		+2,5	3,750 	
75			4,230 	
80	+0,4	+3,0	4,880 	6,133 
90	+0,5	+3,4	6,180 	
100	+0,6	+3,8	7,620 	9,546 
110	+0,7	+4,2	9,210 	
120	+0,8	+4,6	10,910 	13,667 
125			11,900 	
130			12,750 	
140	+0,9	+5,4	14,940 	
150	+1,0	+5,8	17,140 	21,472 
160	+1,1	+6,3	19,500 	
165			20,330 	
180	+1,2	+7,4	24,660 	
200	+1,3	+8,5	30,890 	
225			38,400 	
250		+9,0	47,900 	
280		+9,5	58,200 	
300		+10,0	68,700 	
350		+12,0	93,000 	
400			122,700 	
500			189,000 	
600		+20,0	270,500 	
700			365,700 	

Standardní délky:

- 10 - 130 mm Ø = 2000 mm
- 140 - 700 mm Ø = 1000 mm

Barvy:

-  světle šedá (~RAL 7032)
-  natur
-  černá