

Duté tyče PVC

Rozměry D x d (mm)	Tolerance (mm)				PVC-U kg/m	
	D		d			
	min.	max.	min.	max.		
15 x 5	+ 0,2	+ 0,8	- 0,2	- 0,8	0,246	
20 x 6					0,444	
22 x 6	+ 0,4	+ 1,1	- 0,4	- 1,1	0,574	
25 x 8					0,680	
30 x 10					0,963	
32 x 12					0,980	
35 x 12					1,310	
40 x 15	+ 0,6	+ 2,0	- 0,6	- 2,0	1,660	
45 x 20					1,990	
50 x 20					2,470	
50 x 25					2,230	
55 x 25	+ 0,8	+ 2,5	- 0,8	- 2,5	2,900	
60 x 30					3,450	
70 x 30					4,510	
80 x 30	+ 0,8	+ 3,0	- 0,8	- 3,0	6,540	
80 x 40					5,860	
90 x 60					5,350	
100 x 50	+ 1,2	+ 3,6	- 1,6	- 5,0	8,838	
110 x 60					10,110	
110 x 75					8,220	

120 x 50					14,150 ●
120 x 60	+ 1,5	+ 4,5	- 2,0	- 6,5	12,840 ●
125 x 50					14,963 ●
150 x 50					23,800 ●
160 x 100	+ 1,8	+ 5,4	- 2,2	- 7,5	18,570 ●
200 x 100	+ 2,0	+ 6,0	- 2,5	- 8,5	35,700 ●
230 x 150	+ 3,0	+ 9,0	- 3,0	- 12,0	36,200 ●

Standardní délka:

- 2000 mm

Barva:

- šedá (~RAL 7011)