

Plné tyče PVC

Průměr (mm)	Tolerance průměru (mm)		PVC-U	PVC-C
	min.	max.	kg/m	kg/m
5	+ 0,1	+ 0,4	0,029	
6			0,043	
8		+ 0,5	0,076	
10		+ 0,6	0,118	
12	+ 0,2	+ 0,7	0,170	
15		+ 0,8	0,263	0,300
16			0,299	
18		+ 0,9	0,378	
20		+ 1,0	0,468	0,533
22		+ 1,1	0,525	
25			0,723	0,824
28		+ 1,2	0,890	
30			1,040	1,185
35		+ 1,3	1,350	
40		+ 1,5	1,840	2,097
45	+ 0,3	+ 1,7	2,330	
50		+ 2,0	2,880	3,282
55			3,438	
60		+ 2,3	4,140	4,718
65			4,713	
70		+ 2,5	5,610	6,394
75			6,475	
80			7,300	8,320
85			8,063	
90	+ 0,5	+ 2,8	9,240	10,530
100	+ 0,6	+ 3,0	11,390	12,980
110	+ 0,7		13,760	15,682
120	+ 0,8	+ 3,5	16,390	
125			17,790	20,275
130		+ 4,0	19,260	
140	+ 0,9		22,310	

150	+ 1,0	+ 4,2	25,630   	29,211 * 
160	+ 1,1	+ 4,5	28,300  	
180	+ 1,2	+ 8,0	38,000  	39,400 * 
200	+ 1,3		47,300 	54,000 * 
225			59,900 	
250			71,300 	
280			92,000 	
300	+ 1,5	+ 10,0	106,000 	
350		+ 15,0	142,000 	
400		+ 20,0	185,000 	

Dodací délky:

- 5 - 130 mm Ø = 2000 mm
- 140 - 200 mm Ø = 1000 / 2000 mm
- 225 - 400 mm Ø = 500 / 1000 mm
- PVC-C ≥ 110 mm Ø = 1000 mm

* Tolerance na dotaz

Barvy:

 šedá (~RAL 7011)	 modrá (~RAL 5005)
 červená (~RAL 2002)	 oranžová (~RAL 2007)
 černá (~RAL 9005)	
 světle šedá (~RAL 7040)	
 bílá (~RAL 9010)	