

Plné tyče PA


Průměr (mm)	Tolerance (mm)		PA 6 xt	PA 6 G	PA 6.6	PA 6.6-30G	PA 6.10ECO	PA 12 TR	PA 4.6	PA 6 XAU+	PA LF	
	min.	max.	kg/m	kg/m	kg/m	kg/m	kg/m	kg/m	kg/m	kg/m	kg/m	
6	+0,1	+0,4	0,035 ⊙		0,035 ⊙							
8		+0,5	0,063 ⊙		0,063 ⊙							
10			0,096 ⊙ ●		0,096 ⊙				0,100 ●			
12	+0,2	+0,7	0,141 ⊙		0,141 ⊙							
14												
15			0,217 ⊙									
16		0,246 ⊙ ●		0,246 ⊙					0,256 ●			
18		0,309 ⊙										
20		0,380 ⊙ ●		0,380 ⊙ ●	0,450 ●							
22		+0,9	0,462 ⊙									
25			0,595 ⊙ ●		0,595 ⊙	0,705 ●	0,573 ⊙			0,615 ●		
28			0,740 ⊙		0,740 ⊙							
30			0,850 ⊙ ●		0,850 ⊙ ●	1,007 ●				0,880 ●		
32	+1,1											
36		1,220 ⊙ ●										
40		1,500 ⊙ ●		1,500 ⊙ ●	1,778 ●		1,339 ⊕	1,57 ●				
45	+0,3	+1,3	1,910 ⊙ ●		1,910 ⊙							
50			2,350 ⊙ ●	2,390 ⊙●	2,350 ⊙ ●	2,785 ●	2,266 ⊙		2,45 ●	2,39 ●	2,36 ●	
56			2,930 ⊙ ●								2,99 ●	2,95 ●
60			3,380 ⊙ ●	3,440 ⊙●	3,380 ⊙	4,005 ●				3,52 ●	3,44 ●	3,40 ●
65			3,950 ⊙								4,03 ●	3,98 ●
70			4,640 ⊙ ●	4,800 ⊙●	4,640 ⊙	5,498 ●					4,66 ●	4,60 ●
75			5,300 ⊙								5,39 ●	5,32 ●
80	+0,4	+2,0	6,050 ⊙ ●	6,200 ⊙●	6,050 ⊙	7,169 ●		5,402 ⊕		6,12 ●	6,04 ●	
85	+0,5	+2,2	6,850 ⊙							6,95 ●		
90			7,670 ⊙ ●	7,800 ⊙●	7,670 ⊙						7,77 ●	7,67 ●

95											
100	+ 0,7	+ 3,0	9,450 ⊙ ●	9,800 ⊙●	9,450 ⊙	11,198 ●		8,438 ⊕		9,57 ●	9,45 ●
110			11,500 ⊙	11,700 ⊙●						11,60 ●	11,45 ●
120	+ 0,8	+ 3,8	13,700 ⊙	14,200 ⊙●		16,235 ●				13,80 ●	13,65 ●
125										14,95 ●	14,75 ●
130	+ 0,9	+ 3,8	16,100 ⊙	16,900 ⊙●	16,100 ⊙					16,20 ●	16,00 ●
140			18,700 ⊙	20,000 ⊙						18,75 ●	18,50 ●
150	+ 1,0	+ 4,2	21,400 ⊙	22,500 ⊙●	21,400 ⊙	25,359 ●				21,55 ●	21,25 ●
160	+ 2,0	+ 7,0		25,100 ⊙●						24,90 ●	24,60 ●
170	+ 1,2	+ 5,0		28,400 ⊙							
180			30,800 ⊙	31,500 ⊙●						31,35 ●	30,95 ●
200	+ 1,3	+ 5,5	38,100 ⊙	39,200 ⊙●						38,50 ●	38,00 ●
210											
220	+ 3,0	+ 9,0		48,000 ⊙						47,05 ●	
230				50,600 ⊙							
240										55,70 ●	
250	+ 1,5	+ 6,0		59,800 ⊙●						60,35 ●	59,55 ●
260	+ 3,0	+ 9,0								65,15 ●	
280	+ 1,6	+ 6,5		75,800 ⊙						75,30 ●	
300	+ 1,7	+ 7,0		87,800 ⊙●						86,20 ●	
320				101,500 ⊙							
325										101,8 ●	
350	+ 1,5	+ 12,0		117,500 ⊙						117,7 ●	
400				153,000 ⊙						152,9 ●	
450				195,000 ⊙						194,0 ●	
500				242,000 ⊙						238,5 ●	

Standardní délky:

1000 mm / 3000 mm
 PA 6 G 50 - 80 Ø / 130 - 320 Ø: 1000 mm
 PA 6.6-30GF 150 mm Ø: 1000 mm
 PA 6.10ECO: 3000 mm
 PA 6 XAU+ 160 - 500 Ø: 1000 mm
 PA LFX 160 - 250 Ø: 1000 mm

Barvy:



<input type="radio"/> natur	<input checked="" type="radio"/> zelená
<input type="radio"/> transparentní (čirá)	