

Plné tyče PE

| Průměr (mm) | Tolerance průměru (mm) | | PE-HD | PE-ELS | PE 1000 -UHMW- |
|----------------|---------------------------|--------|-------------|---------|----------------|
| | min. | max. | kg/m | kg/m | kg/m |
| 10 | + 0,1 | + 0,6 | 0,082 ● ○ | | |
| 20 | + 0,2 | + 1,0 | 0,327 ● ○ | | 0,317 ● ○ ● |
| 25 | | + 1,1 | 0,506 ● ○ | | 0,491 ○ |
| 30 | | + 1,2 | 0,720 ● ○ | | 0,703 ● ○ ● |
| 35 | + 0,2 | + 1,3 | 0,988 ● ○ | | 0,970 ○ |
| 40 | | + 1,5 | 1,280 ● ○ | | 1,240 ● ○ ● |
| 45 | + 0,3 | + 1,7 | 1,620 ○ | | 1,570 ○ |
| 50 | | + 2,0 | 2,010 ● ○ | 2,116 ● | 1,950 ● ○ ● |
| 55 | | | 2,360 ● | | |
| 60 | | + 2,3 | 2,880 ● ○ | | 2,800 ● ○ ● |
| 65 | | | 3,370 ○ | | 3,269 ● ○ |
| 70 | | | 3,910 ● ○ | | 3,800 ● ○ ● |
| 75 | | + 2,5 | 4,490 ● | | |
| 80 | + 0,4 | + 3,0 | 5,100 ● ○ | 5,368 ● | 4,947 ● ○ ● |
| 90 | + 0,5 | + 3,4 | 6,450 ● ○ | | 6,264 ● ○ ● |
| 100 | + 0,6 | + 3,8 | 7,960 ● ○ | 8,379 ● | 7,728 ● ○ ● |
| 110 | + 0,7 | + 4,2 | 9,610 ● ○ | | 9,330 ● ○ ● |
| 120 | + 0,8 | + 4,6 | 11,380 ● ○ | | 11,230 ● ○ ● |
| 125 | | | 12,410 ○ | | 12,750 ● ○ ● |
| 130 | | | 13,320 ● ○ | | 13,130 ● ○ ● |
| 140 | + 0,9 | + 5,4 | 15,580 ● ○ | | 15,950 ● ○ ● |
| 150 | + 1,0 | + 5,8 | 17,900 ● ○ | | 17,380 ● ○ ● |
| 160 | + 1,1 | + 6,3 | 20,350 ● ○ | | 19,760 ● ○ ● |
| 180 | + 1,2 | + 7,4 | 25,700 ● ○ | | 24,990 ● ○ ● |
| 200 | + 1,3 | + 8,5 | 32,200 ● ○ | | 31,110 ● ○ ● |
| 225 | | | 42,000 ○ | | |
| 250 | | + 9,0 | 50,000 ● ○ | | |
| 300 | | + 10,0 | 71,800 ● ○ | | |
| 350 | | + 12,0 | 98,000 ● ○ | | |
| 400 | | | 127,000 ● ○ | | |
| 500 | | | 197,000 ● ○ | | |
| 600 | | + 20,0 | 290,000 ● | | |
| 700 | | | 395,000 ● | | |

Standardní délky:

- 10 - 130 mm Ø = 2000 mm
- 140 - 700 mm Ø = 1000 mm

PE-UHMW

- 1000 / 2000 mm

Barvy:

- černá
- natur
- zelená (~RAL 6024)