

Plné tyče PE

Průměr (mm)	Tolerance průměru (mm)		PE-HD	PE-ELS	PE 1000 -UHMW-
	min.	max.	kg/m	kg/m	kg/m
10	+ 0,1	+ 0,6	0,082 ● ○		
20	+ 0,2	+ 1,0	0,327 ● ○		0,317 ● ○ ●
25		+ 1,1	0,506 ● ○		0,491 ○
30		+ 1,2	0,720 ● ○		0,703 ● ○ ●
35	+ 0,2	+ 1,3	0,988 ● ○		0,970 ○
40		+ 1,5	1,280 ● ○		1,240 ● ○ ●
45	+ 0,3	+ 1,7	1,620 ○		1,570 ○
50		+ 2,0	2,010 ● ○	2,116 ●	1,950 ● ○ ●
55			2,360 ●		
60		+ 2,3	2,880 ● ○		2,800 ● ○ ●
65			3,370 ○		3,269 ● ○
70		+ 2,5	3,910 ● ○		3,800 ● ○ ●
75			4,490 ●		
80	+ 0,4	+ 3,0	5,100 ● ○	5,368 ●	4,947 ● ○ ●
90	+ 0,5	+ 3,4	6,450 ● ○		6,264 ● ○ ●
100	+ 0,6	+ 3,8	7,960 ● ○	8,379 ●	7,728 ● ○ ●
110	+ 0,7	+ 4,2	9,610 ● ○		9,330 ● ○ ●
120	+ 0,8	+ 4,6	11,380 ● ○		11,230 ● ○ ●
125			12,410 ○		12,750 ● ○ ●
130			13,320 ● ○		13,130 ● ○ ●
140	+ 0,9	+ 5,4	15,580 ● ○		15,950 ● ○ ●
150	+ 1,0	+ 5,8	17,900 ● ○		17,380 ● ○ ●
160	+ 1,1	+ 6,3	20,350 ● ○		19,760 ● ○ ●
180	+ 1,2	+ 7,4	25,700 ● ○		24,990 ● ○ ●
200	+ 1,3	+ 8,5	32,200 ● ○		31,110 ● ○ ●
225			42,000 ○		
250		+ 9,0	50,000 ● ○		
300		+ 10,0	71,800 ● ○		
350		+ 12,0	98,000 ● ○		
400			127,000 ● ○		
500			197,000 ● ○		
600		+ 20,0	290,000 ●		
700			395,000 ●		

Standardní délky:

- 10 - 130 mm Ø = 2000 mm
- 140 - 700 mm Ø = 1000 mm

PE-UHMW

- 1000 / 2000 mm

Barvy:

- černá
- natur
- zelená (~RAL 6024)