

Plné tyče POM

Průměr	Tolerance (mm)		POM-C	POM-ELS	POM-ESD-FG	POM-10PE
(mm)	min.	max.	kg/m	kg/m	kg/m	kg/m
5	+ 0,1	+ 0,6	0,032 ○●			
6			0,045 ○●			
8		+ 0,7	0,079 ○●			
10			0,121 ○●			
12	+ 0,2	+ 0,8	0,176 ○●			
15			0,271 ○●			
16			0,307 ○●			
18			0,386 ○●			
20			0,474 ○●			0,460 ●
22		+ 1,0	0,575 ○●			
25			0,740 ○●			
28			0,930 ○●			
30			1,060 ○●	1,053 ●		1,043 ●
32		+ 1,2	1,210 ○●			
35			1,440 ○			
36			1,520 ○●			
40			1,870 ○●			1,831 ●
45			2,370 ○●			
50	+ 0,3	+ 1,3	2,920 ○●●	2,900 ●	2,962 ◎	2,864 ●
56			3,650 ○●			
60			4,200 ○●●			4,123 ●
65		+ 1,6	4,920 ○●			
70			5,690 ○●●			
75	+ 0,4	+ 2,0	6,570 ○●			
80			7,460 ○●	7,408 ●		
85	+ 0,5	+ 2,2	8,430 ○●			
90			9,430 ○●			
100	+ 0,6	+ 2,5	11,650 ○●			11,458 ●
110	+ 0,7	+ 3,0	14,150 ○●			
120	+ 0,8	+ 3,5	16,900 ○●			
125			18,300 ○●			
130	+ 0,9	+ 3,8	19,800 ○●			
140			22,900 ○●			
150	+ 1,0	+ 4,2	26,350 ○●			
160	+ 1,1	+ 4,5	30,000 ○●			
165	+ 1,2	+ 5,0	31,200 ○●			
180			37,900 ○●			
200	+ 1,3	+ 5,5	46,800 ○●			
210	+ 1,5	+ 6,2	51,970 ○●			
230			61,900 ○●			
250			72,900 ○●			

300	0	+ 7,5	108,700	●●			
350		+ 8,5	145,600	●●			
400		+ 9,5	189,700	●●			
500		+ 11,5	287,400	●●			

Standardní délky:

1000 / 2000 / 3000 mm

Barvy:

- černá
- natur
- modrá (~RAL 5002)
- slonová kost
- světle modrá