

# Plné tyče PVC

Průměr (mm)	Tolerance průměru (mm)		PVC-U	
	min.	max.	kg/m	
5	+ 0,1	+ 0,4	0,029	
6			0,043	
8		+ 0,5	0,076	
10		+ 0,6	0,118	
12	+ 0,2	+ 0,7	0,170	
15		+ 0,8	0,263	
16			0,299	
18		+ 0,9	0,378	
20		+ 1,0	0,468	
22		+ 1,1	0,525	
25			0,723	
28		+ 1,2	0,890	
30			1,040	
35		+ 1,3	1,350	
40	+ 1,5	1,840		
45	+ 0,3	+ 1,7	2,330	
50		+ 2,0	2,880	
55			3,438	
60		+ 2,3	4,140	
65			4,713	
70		+ 2,5		5,610
75				6,475
80				7,300
85	+ 0,4		8,063	
90	+ 0,5	+ 2,8	9,240	
100	+ 0,6	+ 3,0	11,390	
110	+ 0,7		13,760	
120	+ 0,8	+ 3,5	16,390	
125				17,790
130			+ 4,0	19,260
140	+ 0,9		22,310	
150	+ 1,0	+ 4,2	25,630	
160	+ 1,1	+ 4,5	28,300	
180	+ 1,2	+ 8,0	38,000	
200	+ 1,3			47,300
225				59,900

250	+ 1,5		71,300 ●	
280			92,000 ●	
300			+ 10,0	106,000 ●
350			+ 15,0	142,000 ●
400			+ 20,0	185,000 ●

## Dodací délky:

- 5 - 130 mm Ø = 2000 mm
  - 140 - 200 mm Ø = 1000 / 2000 mm
  - 225 - 400 mm Ø = 500 / 1000 mm
- \* Tolerance na dotaz

## Barvy:

● šedá (~RAL 7011)	● modrá (~RAL 5005)
● červená (~RAL 2002)	● oranžová (~RAL 2007)
● černá (~RAL 9005)	
● světle šedá (~RAL 7040)	
● bílá (~RAL 9010)	