

# Plné tyče PVC

Průměr (mm)	Tolerance průměru (mm)		PVC-U	PVC-C	
	min.	max.	kg/m	kg/m	
5	+ 0,1	+ 0,4	0,029		
6			0,043		
8		+ 0,5	0,076		
10		+ 0,6	0,118		
12	+ 0,2	+ 0,7	0,170		
15		+ 0,8	0,263	0,300	
16			0,299		
18		+ 0,9	0,378		
20		+ 1,0	0,468	0,533	
22		+ 1,1		0,525	
25				0,723	0,824
28				0,890	
30			+ 1,2	1,040	1,185
35		+ 1,3	1,350		
40	+ 1,5	1,840	2,097		
45	+ 0,3	+ 1,7	2,330		
50		+ 2,0		2,880	3,282
55				3,438	
60		+ 2,3		4,140	4,718
65				4,713	
70		+ 2,5		5,610	6,394
75				6,475	
80	+ 0,4			7,300	8,320
85			8,063		
90	+ 0,5	+ 2,8	9,240	10,530	
100	+ 0,6	+ 3,0	11,390	12,980	
110	+ 0,7			13,760	15,682
120	+ 0,8	+ 3,5	16,390		
125				17,790	20,275
130		+ 4,0		19,260	
140	+ 0,9			22,310	

150	+ 1,0	+ 4,2	25,630 ●●●	29,211 *
160	+ 1,1	+ 4,5	28,300 ●●	
180	+ 1,2	+ 8,0	38,000 ●●	39,400 *
200	+ 1,3		47,300 ●	54,000 *
225			59,900 ●	
250			71,300 ●	
280			92,000 ●	
300	+ 1,5	+ 10,0	106,000 ●	
350		+ 15,0	142,000 ●	
400		+ 20,0	185,000 ●	

## Dodací délky:

- 5 - 130 mm Ø = 2000 mm
- 140 - 200 mm Ø = 1000 / 2000 mm
- 225 - 400 mm Ø = 500 / 1000 mm
- PVC-C ≥ 110 mm Ø = 1000 mm

\* Tolerance na dotaz

## Barvy:

● šedá (~RAL 7011)	● modrá (~RAL 5005)
● červená (~RAL 2002)	● oranžová (~RAL 2007)
● černá (~RAL 9005)	
● světle šedá (~RAL 7040)	
○ bílá (~RAL 9010)	