

Plné tyče POM

Průměr	Tolerance (mm)		POM-C	POM-ELS	POM-ESD-FG	POM-10PE
(mm)	min.	max.	kg/m	kg/m	kg/m	kg/m
5	+ 0,1	+ 0,6	0,032 ⊙ ●			
6			0,045 ⊙ ●			
8		+ 0,7	0,079 ⊙ ●			
10			0,121 ⊙ ●			
12	+ 0,2	+ 0,8	0,176 ⊙ ●			
15			0,271 ⊙ ●			
16			0,307 ⊙ ●			
18			0,386 ⊙ ●			
20			0,474 ⊙ ●			0,460 ●
22		+ 1,0	0,575 ⊙ ●			
25			0,740 ⊙ ●			
28			0,930 ⊙ ●			
30			1,060 ⊙ ●	1,053 ●		1,043 ●
32		+ 1,2	1,210 ⊙ ●			
35			1,440 ⊙			
36			1,520 ⊙ ●			
40			1,870 ⊙ ●			1,831 ●
45			2,370 ⊙ ●			
50	+ 0,3	+ 1,3	2,920 ⊙ ● ●	2,900 ●	2,962 ⊙	2,864 ●
56			3,650 ⊙ ●			
60		+ 1,6	4,200 ⊙ ● ●			4,123 ●
65			4,920 ⊙ ●			
70			5,690 ⊙ ● ●			
75	+ 0,4	+ 2,0	6,570 ⊙ ●			
80			7,460 ⊙ ●	7,408 ●		
85	+ 0,5	+ 2,2	8,430 ⊙ ●			
90			9,430 ⊙ ●			
100	+ 0,6	+ 2,5	11,650 ⊙ ●			11,458 ●
110	+ 0,7	+ 3,0	14,150 ⊙ ●			
120	+ 0,8	+ 3,5	16,900 ⊙ ●			
125			18,300 ⊙ ●			
130	+ 0,9	+ 3,8	19,800 ⊙ ●			
140			22,900 ⊙ ●			
150	+ 1,0	+ 4,2	26,350 ⊙ ●			
160	+ 1,1	+ 4,5	30,000 ⊙ ●			
165	+ 1,2	+ 5,0	31,200 ⊙ ●			
180			37,900 ⊙ ●			
200	+ 1,3	+ 5,5	46,800 ⊙ ●			
210	+ 1,5	+ 6,2	51,970 ⊙ ●			
230			61,900 ⊙ ●			
250			72,900 ⊙ ●			

300	0	+ 7,5	108,700	●	●			
350		+ 8,5	145,600	●	●			
400		+ 9,5	189,700	●	●			
500		+ 11,5	287,400	●	●			

Standardní délky:

1000 / 2000 / 3000 mm

Barvy:

- černá
- natur
- modrá (~RAL 5002)
- slonová kost
- světle modrá