

Plné tyče PVC

Průměr (mm)	Tolerance průměru (mm)		PVC-U
	min.	max.	kg/m
5	+ 0,1	+ 0,4	0,029 
6			0,043 
8		+ 0,5	0,076 
10		+ 0,6	0,118   
12	+ 0,2	+ 0,7	0,170 
15		+ 0,8	0,263   
16			0,299 
18		+ 0,9	0,378 
20		+ 1,0	0,468     
22		+ 1,1	0,525 
25			0,723   
28		+ 1,2	0,890 
30			1,040     
35		+ 1,3	1,350  
40		+ 1,5	1,840     
45	+ 0,3	+ 1,7	2,330 
50		+ 2,0	2,880     
55			3,438 
60		+ 2,3	4,140   
65			4,713 
70		+ 2,5	5,610    
75			6,475 
80			7,300   
85			8,063 
90		+ 2,8	9,240   
100	+ 0,4	+ 3,0	11,390    
110	+ 0,5		13,760  
120	+ 0,6	+ 3,5	16,390   
125			17,790  
130		+ 4,0	19,260  
140	+ 0,7		22,310 
150	+ 0,8	+ 4,2	25,630   
160	+ 0,9	+ 4,5	28,300  
180	+ 1,0	+ 8,0	38,000  
200	+ 1,1		47,300 
225	+ 1,2		59,900 
	+ 1,3		

250	+ 1,5		71,300	●
280			92,000	●
300		+ 10,0	106,000	●
350		+ 15,0	142,000	●
400		+ 20,0	185,000	●

Dodací délky:

- 5 - 130 mm Ø = 2000 mm
- 140 - 200 mm Ø = 1000 / 2000 mm
- 225 - 400 mm Ø = 500 / 1000 mm
- * Tolerance na dotaz

Barvy:

● šedá (~RAL 7011)	● modrá (~RAL 5005)
● červená (~RAL 2002)	● oranžová (~RAL 2007)
● černá (~RAL 9005)	
● světle šedá (~RAL 7040)	
● bílá (~RAL 9010)	