

Duté tyče PVC

 D x d (mm)	Tolerance (mm)				PVC-U
	D		d		
	min.	max.	min.	max.	kg/m
15 x 5	+ 0,2	+ 0,8	- 0,2	- 0,8	0,246 
20 x 6	+ 0,4	+ 1,1	- 0,4	- 1,1	0,444 
22 x 6					0,574 
25 x 8					0,680 
30 x 10					0,963 
32 x 12	+ 0,6	+ 2,0	- 0,6	- 2,0	0,980 
35 x 12					1,310 
40 x 15					1,660 
45 x 20					1,990 
50 x 20					2,470 
50 x 25					2,230 
55 x 25	+ 0,8	+ 2,5	- 0,8	- 2,5	2,900 
60 x 30					3,450 
70 x 30	+ 0,8	+ 3,0	- 0,8	- 3,0	4,510 
80 x 30					6,540 
80 x 40					5,860 
90 x 60	+ 1,2	+ 3,6	- 1,6	- 5,0	5,350 
100 x 50					8,838 
110 x 60					10,110 
110 x 75					8,220 

120 x 50	+ 1,5	+ 4,5	- 2,0	- 6,5	14,150
120 x 60					12,840
125 x 50					14,963
150 x 50					23,800
160 x 100	+ 1,8	+ 5,4	- 2,2	- 7,5	18,570
200 x 100	+ 2,0	+ 6,0	- 2,5	- 8,5	35,700
230 x 150	+ 3,0	+ 9,0	- 3,0	- 12,0	36,200

Standardní délka:

- 2000 mm

Barva:

- šedá (~RAL 7011)