

Plné tyče PVC

Průměr (mm)	Tolerance průměru (mm)		PVC-U	PVC-C
	min.	max.	kg/m	kg/m
5	+ 0,1	+ 0,4	0,029 	
6			0,043 	
8		+ 0,5	0,076 	
10		+ 0,6	0,118   	
12	+ 0,2	+ 0,7	0,170 	
15		+ 0,8	0,263   	0,300 
16			0,299 	
18		+ 0,9	0,378 	
20		+ 1,0	0,468     	0,533 
22		+ 1,1	0,525 	
25			0,723   	0,824 
28			0,890 	
30		+ 1,2	1,040     	1,185 
35		+ 1,3	1,350  	
40		+ 1,5	1,840     	2,097 
45	+ 0,3	+ 1,7	2,330 	
50		+ 2,0	2,880     	3,282 
55			3,438 	
60		+ 2,3	4,140   	4,718 
65			4,713 	
70		+ 2,5	5,610    	6,394 
75			6,475 	
80			7,300   	8,320 
85			8,063 	
90	+ 0,5	+ 2,8	9,240   	10,530 
100	+ 0,6	+ 3,0	11,390    	12,980 
110	+ 0,7		13,760  	15,682 
120	+ 0,8	+ 3,5	16,390   	
125			17,790  	20,275 
130		+ 4,0	19,260  	
140	+ 0,9		22,310 	

150	+ 1,0	+ 4,2	25,630   	29,211 * 
160	+ 1,1	+ 4,5	28,300  	
180	+ 1,2	+ 8,0	38,000  	39,400 * 
200	+ 1,3		47,300 	54,000 * 
225			59,900 	
250			71,300 	
280			92,000 	
300	+ 1,5	+ 10,0	106,000 	
350		+ 15,0	142,000 	
400		+ 20,0	185,000 	

Dodací délky:

- 5 - 130 mm Ø = 2000 mm
- 140 - 200 mm Ø = 1000 / 2000 mm
- 225 - 400 mm Ø = 500 / 1000 mm
- PVC-C ≥ 110 mm Ø = 1000 mm

* Tolerance na dotaz

Barvy:

 šedá (~RAL 7011)	 modrá (~RAL 5005)
 červená (~RAL 2002)	 oranžová (~RAL 2007)
 černá (~RAL 9005)	
 světle šedá (~RAL 7040)	
 bílá (~RAL 9010)	